PSI
PHOENIX SURVEYS, INC.

Cement Bond Log
Gamma Ray - CCL - VDL

Company	Encana Oil & Gas (USA) Inc.
Well	Davis 0-4-9
Field	Wattenberg
County	Weld
State	Colorado

Company Encana Oil & Gas (USA) Inc.
Well Davis 0-4-9
Field Wattenberg
County Weld State Colorado

Location: API #: 05-123-31574-0000
SHL: 2011' FNL & 509' FWL SW NW
BHL: 2590' FNL & 50' FWL SW SW
SEC 9 TWP 2N RGE 66W

Other Services
MAST

Permanent Datum	Ground Level	Elevation	4880	Elevation
Log Measured From	Kelly Bushing			K.B. 4893
Drilling Measured From	Kelly Bushing			D.F. 4892 G.L. 4880

Date	28-Jul-2010
Run Number	1
Depth Driller	7996
Depth Logger	7959
Bottom Logged Interval	7958
Top Log Interval	3800
Open Hole Size	7.875"
Type Fluid	Water
Density / Viscosity	8.34 lb/gal
Max. Recorded Temp.	236 DEGF
Estimated Cement Top	4750
Time Well Ready	N/A
Time Logger on Bottom	N/A
Equipment Number	#54
Location	Ft. Morgan, CO
Recorded By	Sam Hopper
Witnessed By	Tom Cobb

Borehole Record				Tubing Record			
Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size	Wgt/Ft	Top	Bottom
Surface String				
Prot. String				
Production String	4.5"	11.6	Surface	7996
Liner				

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Depth Ref to PSI Tripple Combo Log dated 10-Jul-2010.
Tools ran as per tool sketch.
Run CBL from TD to 200' above Est. TOC.
PSI Est. Cement Top @ 4750'
Run 1K psi Pressure Test CBL Pass from 5500' to 3800'
API #: 05-123-31574-00
Thank you for using Phoenix Surveys!!



Sensor	Offset (ft)	Description	Len (ft)	OD (in)	Wt (lb)
		STNDRD Standard Cable Head	1.00	1.69	1.00
		SDSCENT Centralizer	2.87	2.75	24.00
WVF3 WVF5	12.04 11.04	CBL-Probe (050215)	8.75	2.75	93.00
		SDSCENT Centralizer	2.87	2.75	24.00
CCL GR	3.63 0.90	GR_CCL-SDS (SDSSEMO) GR/CCL (050-GR275-001)	4.92	2.75	60.00

Dataset: encana_davis_0-4-9.db: field/well/run1/pass8
Total Length: 20.41 ft
Total Weight: 202.00 lb
O.D. 2.75 in

PSI
PHOENIX SURVEYS, INC.

1K psi Pressure Pass

Database File: encana_davis_0-4-9.db
Dataset Pathname: pass8
Presentation Format: cbl_dr
Dataset Creation: Wed Jul 28 15:12:39 2010 by Log Std Casedhole 09061
Charted by: Depth in Feet scaled 1:240

324	Travel Time (usec)	225
9	CCL	-1
0	GR (GAPI)	200

0	Amplified Amplitude (mV)	20
0	Amplitude (mV)	100

200 Variable Density 1200

324	Travel Time (usec)	225
9	CCL	-1
0	GR (GAPI)	200

0	Amplified Amplitude (mV)	20
0	Amplitude (mV)	100

200 Variable Density 1200

PSI
PHOENIX SURVEYS, INC.

CBL Main Pass

Database File: encana_davis_0-4-9.db
Dataset Pathname: merge3
Presentation Format: cbl_dr
Dataset Creation: Wed Jul 28 08:16:05 2010
Charted by: Depth in Feet scaled 1:240

324	Travel Time (usec)	225
9	CCL	-1
0	GR (GAPI)	200

0	Amplified Amplitude (mV)	20
0	Amplitude (mV)	100

200 Variable Density 1200

PSI
PHOENIX SURVEYS, INC.

Repeat Section

Database File: encana_davis_0-4-9.db
Dataset Pathname: pass2
Presentation Format: cbl_dr
Dataset Creation: Wed Jul 28 06:46:56 2010 by Log Std Casedhole 09061
Charted by: Depth in Feet scaled 1:240


324 Travel Time (usec) 225
9 CCL -1
0 GR (GAPI) 200
0 Amplified Amplitude (mV) 20
0 Amplitude (mV) 100
200 Variable Density 1200
7800
7900
324 Travel Time (usec) 225
9 CCL -1
0 GR (GAPI) 200
0 Amplified Amplitude (mV) 20
0 Amplitude (mV) 100
200 Variable Density 1200