PSL
Petrophysical Solutions Limited
Unit 1, Bridge Street Business Park, Bridge Street, Aberdeen, AB11 6JL
Tel: 01224 584142 Fax: 01224 584143
Email: info@psloffice.com

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, cost, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our General Terms and Conditions as set out in our current price schedule.

Comments

Annular volume calculated for 4.5" casing
Cale Drilling Rig 22
Tricone bit (Hughes Christensen)?
API # 05-23-34444-00

Calibration Time 11:03:38
Calibration Depth 3000'
Calibration Fluid WAT
Density 8.34 lb/gal @ 70.00 °F (20.00 °C)
Viscosity 1.00 cP @ 68.00 °F (20.00 °C)

Density Caliper (in) 16 | Deep Resistivity (Ohmm) .2K | Density Porosity (pu)
Gamma Ray (cAPI) 150 | Medium Resistivity (Ohmm) .2K | Neutron Porosity (pu)
Shallow Resistivity (Ohmm) .2K | Neutron Porosity (pu)