

Well

Operator
Location
API
County
State
Field
Footages

STATE PETERSON #11-20

EnCana Oil & Gas (USA) Inc.
NW NW SECTION 20-T5N-R63W
05-123-25624
Weld
Colorado
Wattenberg
648' FNL & 676' FWL

Spud Date 03-26-2005
TD Date 03-31-2005

Log Tops

Sharon Springs	6277.8'
Niobrara	6348.6'
Codell	6617.5'
J Sand	7050.3'
Log TD	7297.0'

Production Casing and Cement

4 1/2" landed @ 7295'
Cemented with 481 sxs

2 3/8" tubing set @ 6610'
on 04/04/12

CFP

Set @ 6516 on 1/4/2012
Drilled out on 4/3/2012

CIBP

Set @ 6665' on 1/4/2012

CFP

Set @ 6570'

CFP

Set @ 6700'
Drilled out on 07-19-05

Pushed the remainder of CFP
down to 6630'
Drilled out on 07-21-05

Surface Casing

8-5/8" landed @ 417'
Cemented with 200 sxs

Niobrara Refrac

Refrac'd 6350' – 6370' with
136,003 gal frac fluid and 250,840#
sand (01-04-12)

Codell Refrac

Refrac'd 6618' – 6630' with
119,738 gal frac fluid
and 249,480# sand (01-04-12)

Niobrara Perfs

6350' – 6370', 5 spf, 96 holes
6536' – 6560', 3 spf, 80 holes

Frac'd with 201,000 gal frac fluid
and 288,040# 20/40 sand and
12,000# 16/30 RCS (07-22-05)

Codell Perfs

6618' – 6630', 4 spf, 48 holes
Frac'd with 134,474 gal frac fluid
and 300,000# sand (07-14-05)

J Sand Perfs

7050' – 7070', 7085' – 7140', 2 spf,
150 holes
Frac'd the J Sand (7050' – 7140')
with 207,862 gal frac fluid and
300,700# sand (04-10-05)

7300' — Driller's
TD

