PIONEER

Pioneer Energy Services

HIGH RESOLUTION ELECTRO-CORROSION/DEFORMATION PRODUCTION LOG

Company: Rockville Extraction and Production
Well: Hillcrest 3H
Field: Hillcrest
County: Idaho
State: Idaho
Elevation: 1,842 ft KB
Permanent Datum: KB
Log Measured From: KB
Drilling Measured From: KB

Run No.	Date	Depth Driller	Depth Logger	Bottom Logged Interval	Top Logged Interval	Casing Driller	Casing Logger	Bit Size
1	2/22/2021	9,842 ft	9,840 ft	9,838 ft	4,200 ft	9,842 ft	9,840 ft	6.125 in

Type Fluid in Hole: Brine
Density: 9.2 ppg
Viscosity: 38 sec
Fluid Level: 1,200 ft
Max Recorded Temp: 218 °F
Max Surface Pressure: 2,450 psi
Equipment No.: PE-HRECL-07
Location: Hillcrest Pad, Section 14, T12N-R4W
Recorded By: J. Whitfield
Witnessed By: M. Okafor

Comments:

Annular volume calculated for 4-1/2" casing
Ecogyr Drilling Rig 7
Thank you for using Pioneer Energy!

Deep and Medium tool healing up in Niobrara and Codell

Density Caliper (in) 6 … 16
Gamma Ray (GAPI) 0 … 150
SP (mV) -80 … 80
Apparent Resistivity (Ohm-m) .2 … 2000
Medium Resistivity (Ohm-m) .2 … 2000
Shallow Resistivity (Ohm-m) .2 … 2000
Bit Collar (in) 6 … 16
Density Porosity (pu) 45 … -15
Neutron Porosity (pu) 45 … -15

Gamma Ray
Neutron Porosity
Shallow Resistivity
Medium Resistivity
Deep Resistivity
Density Porosity

Logged TD: 9,840'

7,100 KB Marker
7,150
7,200
7,250
7,300
7,350
7,400
7,450
7,500
7,550
7,600
7,650
7,700
7,750
7,800
7,850
7,900
7,950
8,000
8,050
8,100
8,150
8,200
8,250
8,300
8,350
8,400
8,450
8,500
8,550
8,600
8,650
8,700
8,750
8,800
8,850
8,900
8,950
9,000
9,050
9,100
9,150
9,200
9,250
9,300
9,350
9,400
9,450
9,500
9,550
9,600
9,650
9,700
9,750
9,800
9,840 TD

Calculations File: 5177E-4B
Observer Performed: J. Whitfield
Preparation Date: 2/21/2021
Observer Checked: Date: Jan 14 01:23 (MST 2021)
Observer Approved: Date: Jan 14 01:23 (MST 2021)

Density Caliper (in) 6 … 16
Gamma Ray (GAPI) 0 … 150
SP (mV) -80 … 80
Apparent Resistivity (Ohm-m) .2 … 2000
Medium Resistivity (Ohm-m) .2 … 2000
Shallow Resistivity (Ohm-m) .2 … 2000
Bit Collar (in) 6 … 16
Density Porosity (pu) 45 … -15
Neutron Porosity (pu) 45 … -15

Gamma Ray
Neutron Porosity
Shallow Resistivity
Medium Resistivity
Deep Resistivity
Density Porosity

Logged TD: 9,840'

7,100 KB Marker
7,150
7,200
7,250
7,300
7,350
7,400
7,450
7,500
7,550
7,600
7,650
7,700
7,750
7,800
7,850
7,900
7,950
8,000
8,050
8,100
8,150
8,200
8,250
8,300
8,350
8,400
8,450
8,500
8,550
8,600
8,650
8,700
8,750
8,800
8,850
8,900
8,950
9,000
9,050
9,100
9,150
9,200
9,250
9,300
9,350
9,400
9,450
9,500
9,550
9,600
9,650
9,700
9,750
9,800
9,840 TD