

OFFICE OF STATE OIL INSPECTOR  
SUMMARY NOTICES AND REPORTS OF WELLS  
LOCATED ON PRIVATE LANDS



(Indicate nature of data by checking below)



00267193

Notice of intention to drill ☒  
Notice of intention to change plans \_\_\_\_\_  
Notice of date for test of water shut-off \_\_\_\_\_  
Report on result of test of water shut-off \_\_\_\_\_  
Notice of intention to re-drill or repair well \_\_\_\_\_  
Notice of intention to clean out well \_\_\_\_\_  
Statement of shooting \_\_\_\_\_  
Statement of perforating \_\_\_\_\_  
Notice to pull or otherwise alter casing \_\_\_\_\_  
Notice of intention to abandon well \_\_\_\_\_  
Report of work done on well since previous report \_\_\_\_\_

Following is a (notice of intention to do work) (On Land)  
(report of work done) (produced) described as follows:

COLORADO LOGAN YENTER  
State County Field  
6 ZIEGLER "A" (Lot 9) Sec. 2 8N 54W  
(Well No.) (Lease) (Sec. and 1/4 Sec.) (Twp.) (Range) (Meridian)  
The well is located 330 ft. (N) of South and 990 ft. (E) of W  
(XX) (XX)  
Sec. 2 (Lot 9)

The elevation above sea level is 4280 ft. KB Est.

Details of Plan of Work: (State names of and expected depths to objective sands;  
Show sizes, weights, and lengths of proposed casings; indicate casing jobs, cement-  
ing points, and all other important proposed work.)

To drill and test subject well to the "J" Sand of the Graneros Series.

SURFACE CASING: 9-5/8" Armco Spiral Weld to be set at approximately 214' K.B. and cemented with 160 ~~sax~~ Regular cement. Cement to be circulated to ground surface.

PRODUCTION STRING CASING: 5 1/2" OD, 15.5#, J-55 casing to be set thru the oil producing section of the "J" Sand. Cement with 250 sax.

TESTING: 1. No coring planned. 2. DST zones as warranted by samples and Electric Log.

LOGGING: One-run Schlumberger Electric Log from under surface casing to T.D. Run Micro-Log on any significant show in "D" & "J" Sands.

DRIFT SURVEYS: At 50' intervals to 300', thereafter at 250' intervals.

DRILLING TIME: Use geograph starting at 4000'.

SAMPLES: 1. 10' samples from 4400 to 5000'. 2. 5' samples from 5000' to T.D.

DEPTH MEASUREMENTS: SLM of Drill pipe every trip below 3500'.

COMPLETION: Drill "J" Sand to minus 880' T.D. Set and cement oil string casing 1' off bottom and perforate for production.

EXPECTED FORMATION TOPS: Niobrara 4275'; Ft. Hays 4515'; Greenhorn 4745'; "D" Sand 5006';  
"J" Sand 5117'.

SEP 2 1952

J. J. Zwick

DIRECTOR

Colorado Oil and Gas Conservation Commission  
1136 Speer Blvd.  
Denver 4, Colorado

Company The British American Oil Prod. Co.

Address P. O. Box 620, Casper, Wyoming

By Thomas M. Hogan  
Thomas M. Hogan

Title District Superintendent

Submit reports of proposed work, for approval, on this form in duplicate.