



Job Number: SVGJ-160202
Company: PDC
Lease/Well: Skurich Roth 23-6
Location: Weld County, CO
Rig Name: MS Energy Slickline
RKB: 0'
G.L. or M.S.L.: GL

State/Country: Colorado/USA
Declination: 8.3°
Grid: East To True North
File name: W:\2016\PDC\GJ\SKURIC~1\236.SVY
Date/Time: 30-Jun-16 / 13:28
Curve Name: Surface - 6600' M.D. (Rate Gyro)
Lat: 40.426681 Long: -104.481741

MS Energy

WINSERVE SURVEY CALCULATIONS
Minimum Curvature Method
Vertical Section Plane .00
Vertical Section Referenced to Wellhead
Rectangular Coordinates Referenced to Wellhead

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
100.00	.19	309.19	100.00	.10	-.13	.10	.17	309.19	.19
200.00	.25	208.10	200.00	.02	-.36	.02	.36	272.72	.34
300.00	.25	189.18	300.00	-.39	-.50	-.39	.63	231.85	.08
400.00	.29	190.56	400.00	-.85	-.58	-.85	1.03	214.09	.04
500.00	.11	177.00	500.00	-1.20	-.62	-1.20	1.35	207.33	.18
600.00	.16	245.67	600.00	-1.35	-.74	-1.35	1.54	208.74	.16
700.00	.22	214.72	700.00	-1.57	-.98	-1.57	1.85	211.97	.12
800.00	.55	195.87	799.99	-2.19	-1.22	-2.19	2.50	209.13	.35
900.00	.50	199.55	899.99	-3.06	-1.50	-3.06	3.41	206.06	.06
1000.00	.48	182.59	999.99	-3.89	-1.66	-3.89	4.23	203.13	.15
1100.00	.30	191.13	1099.98	-4.57	-1.73	-4.57	4.88	200.76	.19
1200.00	.39	213.12	1199.98	-5.11	-1.97	-5.11	5.47	201.07	.16
1300.00	.30	183.93	1299.98	-5.65	-2.17	-5.65	6.06	201.01	.19
1400.00	.20	243.37	1399.98	-5.99	-2.35	-5.99	6.44	201.37	.26

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
1500.00	.29	221.58	1499.98	-6.26	-2.67	-6.26	6.81	203.09	.13
1600.00	.13	249.34	1599.98	-6.49	-2.94	-6.49	7.13	204.40	.19
1700.00	.26	200.80	1699.98	-6.74	-3.13	-6.74	7.43	204.90	.20
1800.00	.15	211.67	1799.98	-7.07	-3.28	-7.07	7.79	204.90	.12
1900.00	.31	218.43	1899.98	-7.39	-3.52	-7.39	8.18	205.45	.16
2000.00	.63	215.74	1999.97	-8.05	-4.01	-8.05	8.99	206.46	.32
2100.00	.67	211.97	2099.97	-8.99	-4.64	-8.99	10.11	207.28	.06
2200.00	1.11	221.17	2199.95	-10.21	-5.58	-10.21	11.64	208.66	.46
2300.00	1.24	221.03	2299.93	-11.76	-6.93	-11.76	13.65	210.52	.13
2400.00	1.33	219.60	2399.91	-13.47	-8.38	-13.47	15.86	211.89	.10
2500.00	1.24	216.54	2499.88	-15.23	-9.77	-15.23	18.09	212.66	.11
2600.00	1.17	216.89	2599.86	-16.92	-11.02	-16.92	20.19	213.08	.07
2700.00	1.10	218.36	2699.84	-18.49	-12.23	-18.49	22.17	213.49	.08
2800.00	1.10	219.79	2799.82	-19.98	-13.44	-19.98	24.08	213.93	.03
2900.00	1.11	218.60	2899.80	-21.47	-14.66	-21.47	26.00	214.32	.03
3000.00	1.18	224.39	2999.78	-22.97	-15.98	-22.97	27.98	214.84	.14
3100.00	.98	222.65	3099.77	-24.33	-17.28	-24.33	29.85	215.39	.20
3200.00	.47	159.26	3199.76	-25.34	-17.72	-25.34	30.92	214.96	.88
3300.00	.67	88.72	3299.75	-25.71	-16.99	-25.71	30.82	213.45	.68
3400.00	.98	70.74	3399.74	-25.42	-15.60	-25.42	29.82	211.53	.40
3500.00	.63	63.93	3499.73	-24.90	-14.30	-24.90	28.71	209.86	.36
3600.00	.66	57.12	3599.73	-24.34	-13.32	-24.34	27.75	208.68	.08
3700.00	.80	49.04	3699.72	-23.57	-12.31	-23.57	26.59	207.57	.17
3800.00	.63	39.67	3799.71	-22.69	-11.43	-22.69	25.41	206.73	.21
3900.00	.75	46.57	3899.70	-21.82	-10.60	-21.82	24.26	205.92	.15
4000.00	.89	64.59	3999.69	-21.03	-9.43	-21.03	23.05	204.14	.29
4100.00	.84	95.24	4099.68	-20.77	-7.99	-20.77	22.25	201.05	.46
4200.00	1.49	96.55	4199.66	-20.98	-5.97	-20.98	21.82	195.89	.65
4300.00	1.84	103.78	4299.62	-21.51	-3.12	-21.51	21.74	188.26	.41
4400.00	1.98	105.16	4399.56	-22.35	.10	-22.35	22.35	179.73	.15
4500.00	2.51	97.00	4499.49	-23.07	3.95	-23.07	23.40	170.29	.62
4600.00	2.79	101.44	4599.38	-23.82	8.50	-23.82	25.29	160.35	.35
4700.00	2.69	103.69	4699.27	-24.85	13.17	-24.85	28.13	152.08	.15
4800.00	1.43	106.48	4799.20	-25.76	16.65	-25.76	30.67	147.13	1.26
4900.00	1.05	121.14	4899.18	-26.59	18.63	-26.59	32.47	144.99	.49

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
5000.00	.69	136.53	4999.16	-27.50	19.83	-27.50	33.90	144.21	.43
5100.00	.29	115.00	5099.16	-28.05	20.47	-28.05	34.72	143.88	.43
5200.00	.27	217.48	5199.16	-28.34	20.56	-28.34	35.01	144.05	.44
5300.00	.33	199.91	5299.16	-28.80	20.31	-28.80	35.24	144.80	.11
5400.00	.93	60.29	5399.16	-28.67	20.92	-28.67	35.49	143.88	1.20
5500.00	1.91	58.87	5499.12	-27.40	23.05	-27.40	35.81	139.93	.98
5600.00	1.23	68.42	5599.09	-26.15	25.48	-26.15	36.51	135.74	.73
5700.00	.68	65.56	5699.07	-25.51	27.02	-25.51	37.15	133.35	.55
5800.00	.57	110.11	5799.07	-25.43	28.02	-25.43	37.84	132.22	.48
5900.00	.30	94.59	5899.06	-25.62	28.75	-25.62	38.51	131.71	.29
6000.00	.09	343.02	5999.06	-25.57	28.99	-25.57	38.65	131.41	.34
6100.00	.07	316.43	6099.06	-25.45	28.92	-25.45	38.53	131.34	.04
6200.00	.48	335.78	6199.06	-25.02	28.71	-25.02	38.08	131.08	.41
6300.00	.47	359.27	6299.06	-24.23	28.53	-24.23	37.43	130.34	.19
6400.00	2.55	117.00	6399.03	-24.83	30.51	-24.83	39.34	129.14	2.80
6500.00	3.65	118.70	6498.88	-27.37	35.28	-27.37	44.65	127.80	1.10
Last Survey Depth Recorded									
6600.00	2.89	123.61	6598.72	-30.29	40.18	-30.29	50.32	127.02	.81