

HALLIBURTON

iCem[®] Service

Laramie Energy LLC

For: Aaron Duncan

Date: Tuesday, July 02, 2019

CC Federal 0697-03-01W Surface PJR

API#05-045-23992-00

Sincerely,

Grand Junction Cement Engineering

2.0 Real-Time Job Summary


2.1 Job Event Log

Type	Seq. No.	Graph Label	Date	Time	Source	DH Density (ppg)	Comb Pump Rate (bbl/min)	PS Pump Press (psi)	Pump Stg Tot (bbl)	Comments
Event	1	Call Out	7/2/2019	07:00:00	USER					REQUESTED ON LOCATION @ 13:00
Event	2	Pre-Convoy Safety Meeting	7/2/2019	09:00:00	USER					ALL HES PRESENT
Event	3	Crew Leave Yard	7/2/2019	09:15:00	USER					1 HT 400 PUMP TRUCK, 1 660 BULK TRUCK, 1 TRANSPORT, 1 550 SERVICE PICKUP
Event	4	Arrive At Loc	7/2/2019	11:30:00	USER					RIG RUNNING CASING WHEN HES ARRIVED AT LOCATION
Event	5	Assessment Of Location Safety Meeting	7/2/2019	11:40:00	USER					MET WITH COMP REP, AND WENT OVER NUMBERS AND JOB PROCEDURE. WALKED AROUND LOCATION AND COLLECTED WATER SAMPLE (PH-7.0, CHLORIDES-500, TEMP-70F). COMP REP WAS OFFERED SDS FOR ALL CHEMICALS USED BY HES. CALIBRATED MUD SCALES ON WATER.
Event	6	Pre-Rig Up Safety Meeting	7/2/2019	11:45:00	USER					ALL HES PRESENT
Event	7	Rig-Up Equipment	7/2/2019	11:50:00	USER					HES RIGGED UP 1 HT 400 PUMP TRUCK, 1 660 BULK TRUCK, 1 CEMENT SILOS, 1 TRANSPORT, 2" DISCHARGE IRON, AND 4" SUCTION HOSE WITHOUT ENTERING RED ZONE.
Event	8	Pre-Job Safety Meeting	7/2/2019	13:30:00	USER					ALL HES EMPLOYEES AND RIG CREW PRESENT. RIG CIRCULATED @ 8.5 BPM PRIOR TO JOB. PRESSURE WAS 50 PSI.

Event	9	Start Job	7/2/2019	13:45:41	COM4					TD 2608', TP 2598', CSG 9 5/8" J-55 36#, SJ 45.03', OH 14.5", MUD 8.8 PPG
Event	10	Prime Lines	7/2/2019	13:46:47	COM4	8.33	2	31	3	FRESH WATER
Event	11	Test Lines	7/2/2019	13:50:06	COM4			3660		ALL LINES HELD PRESSURE AT 3660 PSI
Event	12	Pump H2O Spacer	7/2/2019	13:52:16	COM4	8.33	8	158	190	190BBLS FRESH WATER
Event	13	Pump Lead Cement	7/2/2019	14:18:02	COM4	12.3	8	233	370.6	878 SKS VARICEM CMT 12.3 PPG, 2.4 FT3/SK, 13.8 GAL/SK
Event	14	Check Weight	7/2/2019	14:21:14	USER					WEIGHT VERIFIED VIA PRISSEREIZED MUD SCALES
Event	15	Pump Tail Cement	7/2/2019	15:10:31	COM4	12.8	8	250	94.7	252 SKS VARICEM CMT 12.8 PPG, 2.13 FT3/SK, 11.79 GAL/SK
Event	16	Slow Rate	7/2/2019	15:12:10	USER					SLOWED RATE DUE DELIVERY ISSUES
Event	17	Check Weight	7/2/2019	15:17:53	USER					WEIGHT VERIFIED VIA PRISSEREIZED MUD SCALES
Event	18	Shutdown	7/2/2019	15:27:24	USER					END OF CEMENT, WASH UP ON TOP OF PLUG
Event	19	Pump Displacement	7/2/2019	15:30:09	COM4	8.33	10	520	197.4	FRESH WATER
Event	20	Drop Top Plug	7/2/2019	15:30:59	USER					VERIFIED BY FLAG INDICATOR
Event	21	Slow Rate	7/2/2019	15:52:40	USER	8.33	2	200	187.4	SLOW RATE TO 2 BPM TO BUMP PLUG
Event	22	Bump Plug	7/2/2019	15:56:13	COM4	8.33	2	200	197.4	LAND PLUG AT 190 PSI, BROUGHT UP TO 820 PSI
Event	23	Check Floats	7/2/2019	15:56:45	COM4					FLOATS HELD, .5 BBL BACK TO TRUCK
Event	24	Circulate Parasite line	7/2/2019	16:02:29	COM4	8.33	2	390	10	10BBLS SUGAR WATER
Event	25	Top Out	7/2/2019	17:01:37	USER	15.6	2	110	84	400 SKS TYPE I-II CMT 15.6 PPG, 1.19 FT3/SK, 5.24 GAL/SK. 2 BAGS CALCIUM CHLORIDE AND 5BBLS OF SUPER FLUSH AHEAD. NO CEMENT TO SURFACE, SHUTDOWN AND WAIT 2 HOURS PER CO REP.
Event	26	Top Out	7/2/2019	19:48:54	USER	15.6	2.5	140	20	94 SKS TYPE I-II CMT 15.6 PPG, 1.19 FT3/SK, 5.24 GAL/SK. 6BBLS OF SUPER FLUSH AHEAD.

Event	27	End Job	7/2/2019	19:59:30	COM4	NO RETURNS THROUGHOUT JOB .USED 40# OF SUGAR AND TOP PLUG. NO CEMENT TO SURFACE. TOPPED OUT WELL WITH 104BBLS.
Event	28	Post-Job Safety Meeting (Pre Rig-Down)	7/2/2019	20:10:00	USER	ALL HES PRESENT
Event	29	Rig-Down Equipment	7/2/2019	20:20:00	USER	ALL HES PRESENT
Event	30	Pre-Convoy Safety Meeting	7/2/2019	21:30:00	USER	ALL HES PRESENT
Event	31	Crew Leave Location	7/2/2019	21:45:00	USER	THANK YOU FOR CHOOSING HALLIBURTON CEMENT, SHAWN BLOSSOM AND CREW.

LARAMIE CC FED 0697-03-01W SURFACE



— DH Density (ppg)
 — Comb Pump Rate (bbl/min)
 — PS Pump Press (psi)
 — Pump Stg Tot (bbl)

Description	Actual Time (UTC-06:00:00)	DH Density (ppg)	Comb Pump Rate (bbl/min)	PS Pump Press (psi)	Pump Stg Tot (bbl)
9 Start Job	13:45:41	0.23	0.00	9.00	0.00
10 Prime Lines	13:46:47	8.45	1.60	19.00	0.40
11 Test Lines	13:50:06	8.33	0.00	2074.00	3.10
12 Pump H2O Spacer	13:52:16	8.30	0.00	5.00	0.00
13 Pump Lead Cement	14:18:02	12.14	5.00	136.00	0.00
14 Check Weight	14:21:14	12.27	8.00	230.00	22.80
15 Pump Tail Cement	15:10:31	12.69	8.00	233.00	400.50
16 Slow Rate	15:12:10	13.00	3.10	100.00	10.10
17 Check Weight	15:17:53	12.77	8.00	221.00	28.80
18 Shutdown	15:27:24	12.82	5.90	138.00	99.90
19 Pump Displacement	15:30:09	-0.14	0.00	4.00	0.00
20 Drop Top Plug	15:30:59	8.52	3.70	2.00	2.30
21 Slow Rate	15:52:40	8.33	2.10	219.00	196.10
22 Bump Plug	15:56:13	8.33	0.00	735.00	201.80
23 Check Floats	15:56:45	8.33	0.00	128.00	201.80
24 Circulate Parasite line	16:02:29	-0.15	0.00	10.00	0.00

▼ HALLIBURTON | iCem® Service

Created: 2019-07-02 08:09:15, (UTC-06:00), Version: 5.0.161.0


Edit

Customer : Laramie Energy LLC
 Representative : MATT SETTLES

Job Date : 7/2/2019
 Sales Order # : 905812287


Well : CC FED 0697-03-01W
 ELITE 4 : D.PORTER/S.BLOSSOM

LARAMIE CC FED 0697-03-01W SURFACE



— DH Density (ppg)
 — Comb Pump Rate (bbl/min)
 — PS Pump Press (psi)
 — Pump Stg Tot (bbl)

LARAMIE CC FED 0697-03-01W, TOP OUT



— DH Density (ppg)
 — Comb Pump Rate (bbl/min)
 — PS Pump Press (psi)
 — Pump Stg Tot (bbl)

Description	Actual Time (UTC-06:00:00)	DH Density (ppg)	Comb Pump Rate (bbl/min)	PS Pump Press (psi)	Pump Stg Tot (bbl)
25 Top Out	17:01:37	8.62	1.20	19.00	0.40
26 Top Out	19:48:54	7.82	0.90	11.00	0.20
27 End Job	19:59:30	14.00	0.00	28.00	23.60
28 Post-Job Safety Meeting (Pre Rig-Down)	20:10:00	9.82	0.00	10.00	23.60
29 Rig-Down Equipment	20:20:00	15.58	0.90	48.00	29.20

▼ **HALLIBURTON** | iCem® Service


Created: 2019-07-02 08:09:15, (UTC-06:00), Version: 5.0.161.0 Edit

Customer : Laramie Energy LLC
 Representative : MATT SETTLES

Job Date : 7/2/2019
 Sales Order # : 905812287

Well : CC FED 0697-03-01W
 ELITE 4 : D.PORTER/S.BLOSSOM

LARAMIE CC FED 0697-03-01W, TOP OUT



HALLIBURTON

iCem[®] Service

Laramie Energy LLC

Rock Springs District, Colorado

For: Aaron Duncan

Date: Saturday, July 06, 2019

CC 697-03-01W Production PJR

API# 05-045-23992-00

Sincerely,

Grand Junction Cement Engineering


1.0 Real-Time Job Summary

1.1 Job Event Log

Type	Seq. No.	Graph Label	Date	Time	Source	Recirc Density (ppg)	Comb Pump Rate (bpm)	PSI	Volume (bbl)	Comments
Event	1	Call Out	7/5/2019	20:00:00						Requested on Location @ 03:00
Event	2	Pre-Convoy Safety Meeting	7/5/2019	21:50:00						
Event	3	Crew Leave Yard	7/5/2019	22:00:00						1 Elite, 1 660, 1 pickup
Event	4	Arrive At Loc	7/6/2019	03:00:00						Rig running casing
Event	5	Assessment Of Location Safety Meeting	7/6/2019	03:10:00						JSA completed - Customer offered/received SDS - water test pH 7.0, Cl <200, temp 64 degrees
Event	6	Pre-Rig Up Safety Meeting	7/6/2019	03:20:00						
Event	7	Rig-Up Equipment	7/6/2019	03:33:00						1 hardline to standpipe, water hoses to upright, bulk hoses to silos and 660.
Event	8	Other	7/6/2019	04:00:00						Mud scales calibrated to drinking water prior to job.
Event	9	Pre-Job Safety Meeting	7/6/2019	10:13:00						All HES personnel, rig crew, and company rep
Event	10	Start Job	7/6/2019	10:30:39						TD 10422', TP 10410.5, SJ 87.84', OH 8 3/4", Csg 4.5" 11.6 lb/ft P-110, Mud 9.6 ppg
Event	11	Fill Lines	7/6/2019	10:31:51		8.33	2	50	5	Fresh Water
Event	12	Test Lines	7/6/2019	10:35:16				6350		No Leaks
Event	13	Pump Spacer 1	7/6/2019	10:40:17		8.4	6	180	60	240 lbs. Mud Flush III

Event	14	Check Weight	7/6/2019	10:53:31					Density Verified via Mud Scales, Tub Recirc. Denso. on chart, down hole denso. Was having issues with correct density.
Event	15	Pump Lead Cement	7/6/2019	10:59:20	12.5	8	700	408.7	1183 Sks 12.5 ppg 1.94 yield 9.59 gal/sk
Event	16	Pump Tail Cement	7/6/2019	11:58:56	13.0	8	950	162.2	440 Sks 13.0 ppg 1.94 yield 9.42 gal/sk
Event	17	Shutdown	7/6/2019	12:26:01					Wash lines to pit
Event	18	Drop Top Plug	7/6/2019	12:35:51					Customer verified top plug launched
Event	19	Pump Displacement	7/6/2019	12:37:15	8.33	10	2197	160	1 gal. MMCR, 5 Gal Clay-web.
Event	20	Slow Rate	7/6/2019	12:53:54			2270		Slow Rate 10 bbls to Calculated Displacement
Event	21	Bump Plug	7/6/2019	12:56:18			2830		Plug Bumped at 2270 psi, Brought up to 2830 psi
Event	22	Pressure Test	7/6/2019	12:59:07					10 Min. Casing Test
Event	23	Check Floats	7/6/2019	13:08:57					Floats held – 2 bbl back to the truck
Event	24	Pump Cement	7/6/2019	13:49:28	15.6	3	50	6.3	30 sks, 15.6 ppg, 1.18 Yield, 5.23 gal/sk
Event	25	End Job	7/6/2019	13:56:54					Good returns throughout job, pipe was reciprocated not during cement job. 20 bbl of mud flush to surface
Event	26	Pre-Rig Down Safety Meeting	7/6/2019	14:16:46					40 lbs sugar used, 3 add hour
Event	27	Rig-Down Equipment	7/6/2019	14:22:47					
Event	28	Pre-Convoy Safety Meeting	7/6/2019	15:05:07					
Event	29	Crew Leave Location	7/6/2019	15:12:56					Thank you for using Halliburton – Chris Martinez and crew.


Laramie, CC 697-03-01W, 4 1/2" Production



— Recirc Density (ppg)
 — Comb Pump Rate (bbl/min)
 — DS Pump Press (psi)
 — Pump Stg Tot (bbl)

Description	Actual Time (UTC-06:00:00)	Recirc Density (ppg)	Comb Pump Rate (bbl/min)	DS Pump Press (psi)	Pump Stg Tot (bbl)
10 Start Job	10:30:39	8.54	0.00	-7.00	0.00
11 Fill Lines	10:31:51	8.54	0.00	-4.00	0.00
12 Test Lines	10:35:16	8.54	0.00	22.00	2.60
13 Pump Spacer 1	10:40:17	8.39	1.60	0.00	0.70
14 Check Weight	10:53:31	12.62	2.20	26.00	32.60
15 Pump Lead Cement	10:59:20	12.60	5.90	493.00	1.30
16 Pump Tail Cement	11:58:56	12.82	7.40	553.00	421.90
17 Shutdown	12:26:01	-0.33	0.00	118.00	185.30
18 Drop Top Plug	12:35:51	8.19	0.00	7.00	1.10
19 Pump Displacement	12:37:15	8.19	2.40	14.00	1.40
20 Slow Rate	12:53:54	8.18	4.30	1333.00	157.80
21 Bump Plug	12:56:18	8.18	0.00	1934.00	165.00
22 Pressure Test	12:59:07	8.18	0.00	2574.00	165.40
23 Check Floats	13:08:57	8.18	0.00	660.00	165.40
24 Pump Cement	13:49:28	15.43	1.00	29.00	2.10
25 End Job	13:56:54	-0.33	0.00	0.00	19.80

Laramie, CC 697-03-01W, 4 1/2" Production



Recirc Density (ppg)

Comb Pump Rate (bbl/min)

DS Pump Press (psi)

Pump Stg Tot (bbl)

Job Information

Request/Slurry	2567292/1	Rig Name	H&P 522	Date	01/JUL/2019
Submitted By	Patrick Ealey	Job Type	Production Casing	Bulk Plant	Grand Junction
Customer	Laramie Energy	Location	Garfield	Well	CC Federal 0697-03-01W

Well Information

Casing/Liner Size	4.5 in	Depth MD	10461 ft	BHST	119°C / 247°F
Hole Size	8.75 in	Depth TVD	9807 ft	BHCT	81°C / 177°F
Pressure	6165 psi				

Drilling Fluid Information

Mud Supplier Name		Mud Trade Name		Density	
--------------------------	--	-----------------------	--	----------------	--

Cement Information - Lead Design

<u>Conc</u>	<u>UOM</u>	<u>Cement/Additive</u>	<u>MP</u>	<u>Sample Type</u>	<u>Sample Date</u>	<u>Lot No.</u>	Cement Properties		
		NeoCem Lead					Slurry Density	12.5	lbm/gal
							Slurry Yield	1.95	ft3/sack
							Water Requirement	9.61	gal/sack
							Total Mix Fluid	9.61	gal/sack
							Water Source	Fresh Water	
							Water Chloride		


This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

Operation Test Results Request ID 2567292/1

Thickening Time - ON-OFF-ON, Request Test ID:36631695

04/JUL/2019

Test Temp (degF)	Pressure (psi)	Reached in (min)	30 Bc (hh:min)	50 Bc (hh:min)	70 Bc (hh:min)	100 Bc (hh:min)	Start Bc	Stirring before stop (mins)	Static Period (min)	Peak reading (BC)
177	6165	57	4:49	5:08	5:13	5:22	16	67	15	16



Total SKS = 1183
 CS0784 TR 1513 440 SKS
 CS0785 TR 8476 440 SKS
 no deflection, 16Bc---- > 16Bc


This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

Operation Test Results Request ID 2567292/2

Thickening Time - ON-OFF-ON, Request Test ID:36640831

04/JUL/2019

Test Temp (degF)	Pressure (psi)	Reached in (min)	30 Bc (hh:min)	50 Bc (hh:min)	70 Bc (hh:min)	100 Bc (hh:min)	Start Bc	Stirring before stop (mins)	Static Period (min)	Peak reading (BC)
177	6165	57	4:15	4:58	5:19	5:33	10	67	15	10



Total SKS = 1183
 CS0789 TR#6813, 303 SKS
 no deflection, 10Bc---> 10Bc
 Heat of hydration at 5:13

This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

Job Information

Request/Slurry	2567293/1	Rig Name	H&P 522	Date	01/JUL/2019
Submitted By	Patrick Ealey	Job Type	Production Casing	Bulk Plant	Grand Junction
Customer	Laramie Energy	Location	Garfield	Well	CC Federal 0697-03-01W

Well Information

Casing/Liner Size	4.5 in	Depth MD	10461 ft	BHST	119°C / 247°F
Hole Size	8.75 in	Depth TVD	9807 ft	BHCT	81°C / 177°F
Pressure	6165 psi				

Drilling Fluid Information

Mud Supplier Name	Mud Trade Name	Density
--------------------------	-----------------------	----------------

Cement Information - Tail Design

<u>Conc</u>	<u>UOM</u>	<u>Cement/Additive</u>	<u>MP</u>	<u>Sample Type</u>	<u>Sample Date</u>	<u>Lot No.</u>	Cement Properties		
		NeoCem HT Tail					Slurry Density	13	lbm/gal
							Slurry Yield	2.07	ft3/sack
							Water Requirement	9.42	gal/sack
							Total Mix Fluid	9.42	gal/sack
							Water Source	Fresh Water	
							Water Chloride		


This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

Operation Test Results Request ID 2567293/1

Thickening Time - ON-OFF-ON, Request Test ID:36631697

04/JUL/2019

Test Temp (degF)	Pressure (psi)	Reached in (min)	30 Bc (hh:min)	50 Bc (hh:min)	70 Bc (hh:min)	100 Bc (hh:min)	Start Bc	Stirring before stop (mins)	Static Period (min)	Peak reading (BC)
177	6165	57	1:47	1:55	2:05	2:09	10	67	15	29



Total SKS = 440
 CS0786 TR 0812 340 SKS
 Deflected from 14Bc--- > 29Bc--- > 20 Bc within one minute
 please see the graph , heat of hydration at 1:50


This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

Operation Test Results Request ID 2567293/2

Thickening Time - ON-OFF-ON, Request Test ID:36640829

04/JUL/2019

Test Temp (degF)	Pressure (psi)	Reached in (min)	30 Bc (hh:min)	50 Bc (hh:min)	70 Bc (hh:min)	100 Bc (hh:min)	Start Bc	Stirring before stop (mins)	Static Period (min)	Peak reading (BC)
177	6165	57	1:53	2:00	2:11	2:17	24	67	15	36



Total SKS = 440
 CS0787, TR#1972 100 SKS
 deflected from 14Bc---- > 36Bc--- > 27Bc within one minute.
 Please review the graph for heat of hydration at 1:55

This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.