



OIL AND GAS CONSERVATION COMMISSION  
OF THE STATE OF COLORADO

RECEIVED  
OCT 7 - 1963  
OIL & GAS  
CONSERVATION COMMISSION

SUNDRY NOTICES AND REPORTS ON WELLS

INSTRUCTIONS

Notice must be given to the Director, and approval obtained in advance of the time when the owner or operator expects to recomplate or abandon a well or to change plans. Within thirty (30) days after recompletion, change of plans, or remedial work, a detailed report of the work done and the results obtained shall be submitted on this form in duplicate for wells on Patented and Federal lands, and in triplicate for wells on State lands. In work that affects only rods, pumps or tubing or other routine work such as, but not limited to, cleaning out to previous total depth, no report is necessary.

Notice of Intention to Recomplate	<input type="checkbox"/>	Report of Remedial Work	<input type="checkbox"/>
Notice of Intention to Change Plans	<input type="checkbox"/>	Report of Recompletion	<input type="checkbox"/>
<input checked="" type="checkbox"/> Notice of Intention to Abandon Well	<input checked="" type="checkbox"/>	Other	<input type="checkbox"/>

(Check appropriate space)

LEASE NAME Colorado State "D" WELL NO. 1  
 FIELD Padroni WILDCAT \_\_\_\_\_ COUNTY Logan  
 LOCATION C SW NE Section 16 Township 9N Range 52W Meridian 6th  
 (Quarter Quarter)  
2022 feet from N Section Line and 1972 feet from E Section Line  
 N or S E or W

(DETAILS OF WORK)

10 3/4" OD, 32.75# Surface casing cemented at 187' with 150 sacks.  
 5 1/2" OD, 14# Producing casing cemented at 4616' with 175 sacks. PBTD 4576'.  
 Present perforations 4560-69'.

- Place cement plug from 4576 to at least 4555'.
- Shoot-off casing at about 3500 and salvage.
- Spot heavy mud to bottom of surface casing at 187'.
- Place 15 sacks cement plug in bottom of surface casing.
- Spot heavy mud in surface casing.
- Place 5 sacks cement plug in top of surface casing.
- Cut casing 3' below ground level.
- Weld cap on top of cut-off surface casing.

*Change of plans:  
 Sand to 4500 then place cement plug.  
 to be sure of set-up covering perms.  
 phone call Bob Donnelly 11/13/63 2P.  
 work to commence 11/13/63*

DVR	
WRS	
HHM	
JAM	
FJP	<input checked="" type="checkbox"/>
JJD	<input checked="" type="checkbox"/>
FILE	

I/We hereby swear (or affirm) that the statements herein made are a full and correct report.

APPROVED: [Signature]  
 OCT 8 1963  
 Date  
 Director

Company W. C. McBride, Inc. Date October 4, 1963  
 Address 620 Colorado Bldg., Denver Phone No. 825-2366  
 By David Pauli Title Production Superintendent  
 (Signature)