

CNTY:	<u>Weld</u>	FTG:	<u>990 FNL and 1650 FWL</u>	IP GAS:	<u>0</u>
STATE:	<u>CO</u>	Q-Q:	<u>NENW</u>	IP OIL:	<u>0</u>
ROTARY SPUD:	<u>27-Jun-55</u>	SEC.:	<u>12</u>	IP WTR:	<u>0</u>
COMP/PA:	<u>6-Jul-55</u>	TWS:	<u>7N</u>	CUM GAS:	<u>0</u>
STATUS:	<u>DA</u>	RGE:	<u>59W</u>	CUM OIL:	<u>0</u>
WBD DATE:	<u>31-Aug-21</u>	BY:	<u>SMB</u>	CUM WTR:	<u>0</u>
LAT/LONG:	<u>40.593836/-103.929057</u>			LAST PROD:	<u>n/a</u>

CURRENT WELLBORE DIAGRAM

KBE: 4877 '
KB: 22 '
GLE: 4855 '

Plug #3

TD (ft): 6610 '
PBSD (ft): 0 '

Plug #2

10 3/4" 32# Csg @ 169 ' w/ 150 sxs

Base Fox Hills @	400'
Top Pierre @	1450'
Top Parkman @	3060'
Top Niobrara @	5784'
Top D Sand @	6510'
Top J Sand @	6590'

Plug #1

OPEN HOLE

8-3/4" Hole to 6590 '

TD @ 6610 '
6-1/4" Hole

WCR 119 & Hwy 14. S 1/10. E Into.

CASING HEAD: [None](#)
WELLHEAD: [None](#)

CASING RECORD

HOLE (in)	SIZE (in)	WT (lb/ft)	GRADE	TOP (ft)	BTM (ft)	JTS
12 1/4	10 3/4	32		0	169	

Float Collar @

TUBING RECORD

COND: _____ DATE: _____

<u>SIZE (in)</u>	<u>WT (lb/ft)</u>	<u>GRADE</u>	<u>TOP (ft)</u>	<u>TALLY (ft)</u>	<u>JTS</u>

[illegible]

PERFORATION RECORD

[illegible]

WELLWORK HISTORY

DA since 1955

Plug 1 = 20 sx from 6560 to 6500

Plug 2 = 10 sx from 160 to 140

Plug 3 = 5 sx at surface