

13  
RECEIVED  
AUG 25 1952  
OIL & GAS  
CONSERVATION COMMISSION

Locate  
Well  
Correctly

DIRECTOR OF STATE OIL INSPECTOR  
Oil and Gas Conservation  
Department

LOG OF OIL AND GAS WELL

M. Smith #1



230

4-22

Company British-American Oil Producing Co. Address Casper, Wyoming - P. O. Box 620  
State or Patented Patented Field West Peetz State Colorado  
Well No. 1 Sec. 29 T. 12N. R. 52W. Meridian County Logan  
Location 330 Ft. XXX of S. Line and 330 Ft. XXX of W. Line of SW/4 Elevation  
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.  
Signed *Thomas Rustogen*  
Title District Superintendent  
Date August 21, 1952

The summary on this page is for the condition of the well as above data.  
Commenced drilling 4-28, 19 52 Finished drilling 5-13 1952

OIL SANDS OR ZONES  
No. 1, from 5124 to 5172  
No. 2, from 5252 to 5299  
No. 3, from to  
No. 4, from to  
No. 5, from to  
No. 6, from to  
IMPORTANT WATER SANDS  
No. 1, from to  
No. 2, from to  
No. 3, from to  
No. 4, from to

CASING RECORD									
Size	Weight per ft.	Threads per inch	Make	Amount	Kind of Shoe	Cut & Pulled from	Perforated From	To	Purpose
9-5/8"	25.4		Armco	200					
5 1/2"	15.5	8 Rd.	J-55	5218			5150	5154	Squeezed off W/cement.
							5140	5146	" " " "
							5126	5132	" " " "

MUDDING AND CEMENTING RECORD					
Size	Where Set	No. Sacks of Cement	Methods used	Mud Gravity	Amount of Mud Used
9-5/8"	214' KB	180	HOWCO		
5 1/2"	5218' KB	200	HOWCO		

PLUGS AND ADAPTERS  
Leaving plug-Material Length Depth Set  
Adapters-Material Size

SHOOTING RECORD					
Size	Shell Used	Explosive Used	Quantity	Date	Depth shot Depth cleared out

TOOLS USED  
Rotary tools used from 0 ft. to 5330 ft. and from ft. to ft.  
Cable tools were used from 5156 ft. to 5182 ft. and from 5079 ft. to 5143 ft.

DATES  
Tested 6-30 19 52  
The production for the first 24 hours was  
% gas oil, % emulsion, % sediment. Gravity 86.  
\* If gas well, cu. ft. per 24 hours 2,800,000  
of gas. Rock pressure, lbs. per sq. in.

STERLING DRILLING COMPANY

FORMATION RECORD			
From	To	Total Feet	Formation
0	222	222	Surface clay and gravel.
222	1225	1003	Shale and bentonite steaks.
1225	2570	1345	Shale and shells.
2570	5045	2475	Shale and lime.
5045	5123	78	Shale and sandy shale.
5123	5172	49	Sand.
5172	5252	80	Shale and sandy shale.
5252	5299	47	Sand.
5299	5330	31	Sandy shale and shale.

\* Shut in Gas Well.