



OFFICE OF STATE OIL INSPECTOR
SUNDRY NOTICES AND REPORTS OF WELLS
LOCATED ON PRIVATE LANDS

BEST IMAGE
AVAILABLE

MAR 25 1952

293-4

(Indicate nature of data by checking below)



Notice of intention to drill X
Notice of intention to change plans _____
Notice of date for test of water shut-off _____
Report on result of test of water shut-off _____
Notice of intention to re-drill or repair well _____
Notice of intention to clean out well _____
Statement of shooting _____
Statement of perforating _____
Notice to pull or otherwise alter casing _____
Notice of intention to abandon well _____
Report of work done on well since previous report _____

Following is a (notice of intention to do work) (On land) 19_____
(patented) described as follows:

COLORADO	LOGAN	WALKER			
State	County	Field			
4	RAMEY	NW/4 Sec. 21	9N	53W	(Well No.) (Lease) (Sec. and 1/4 Sec.) (Twp.) (Range) (Meridian)

The well is located 990 ft. (XX) of North Line and 330 ft. (XX) of East Line
(S) (W)
NW/4 Sec. 21, 9N, 53W

The elevation above sea level is 4114 ft. KB Est.

Details of Plan of Work: (State names of and expected depths to objective sands:
Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
ing points, and all other important proposed work.)

To drill & test subject well to the "J" Sand of the Graneros series.

SURFACE CASING: 9-5/8" OD Armco Spiral Weld set at 210' KB and cemented with 160 sax. regular cement circulated to surface.

PRODUCTION STRING CASING: Run 5 1/2" OD 15.5# J-55 casing thru the oil producing section of the "J" Sand. Cement with 250 sax.

TESTING: 1. No cores recommended. 2. DST "J" Sand if warranted by samples & electric log.

LOGGING: Schlumberger electric log from under surface casing to TD including detail & Micro-log of "D" & "J" Sands.

DRIFT SURVEYS: At 50' intervals to 300'. Thereafter at 250' intervals.

DRILLING TIME: Use Geolograph from 1000'.

SAMPLES: At discretion of Geologist.

DEPTH MEASUREMENTS: SLM of Drill pipe at 4000', before DST & at T.D.

COMPLETION PROGRAM: Brill "J" Sand to -798', set casing 1' off bottom and cement. Perforate for production.

EXPECTED FORMATION TOPS: Niobrara 3980'; Ft. Hays 4268'; Carlile 4322'; Greenhorn 4534';
"D" Sand 4771'; "J" Sand 4874'.

Approved:

MAR 25 1952

State Oil Inspector
Director

Company The British American Oil Producing Co.

Address P. O. Box 620, Casper, Wyoming

By

Wm. Evelyn, Jr.

Title Sup't., Northwestern District

Submit reports of proposed work, for approval, on this form in Duplicate.