



OIL AND GAS CONSERVATION COMMISSION
OF THE STATE OF COLORADO

SUNDRY NOTICES AND REPORTS ON WELLS

OIL & GAS
CONSERVATION COMMISSION

INSTRUCTIONS

Notice must be given to the Director, and approval obtained in advance of the time when the owner or operator expects to recomplate or abandon a well or to change plans. Within thirty (30) days after recompletion, change of plans, or remedial work, a detailed report of the work done and the results obtained shall be submitted on this form in duplicate for wells on Patented and Federal lands, and in triplicate for wells on State lands. In work that affects only rods, pumps or tubing or other routine work such as, but not limited to, cleaning out to previous total depth, no report is necessary.

Notice of Intention to Recomplate	<input type="checkbox"/>	Report of Remedial Work	<input type="checkbox"/>
Notice of Intention to Change Plans	<input type="checkbox"/>	Report of Recompletion	<input type="checkbox"/>
Notice of Intention to Abandon Well	<input type="checkbox"/>	Other Progress Report	<input checked="" type="checkbox"/>

(Check appropriate space)

LEASE NAME H. Flader WELL NO. 2
 FIELD Busy Bee WILDCAT _____ COUNTY Adams
 LOCATION SW NE Section 9 Township 3 S. Range 60 W. Meridian 6th P.M.
 (Quarter Quarter)
 feet from _____ Section Line and _____ feet from _____ Section Line
 N or S _____ E or W _____

(DETAILS OF WORK)

Spud December 3, 1958, surface 3 joints 8 5/8" 24# J-55 landed at 113.54 K.B. cemented with 100 sacks, regular. Schlumberger tops Niobrora 5632, Ft. Hays 5970, Greenhorn 6078 "D" 6411, J6469 T.D. 6525.

Core Data

Core #1 6418-34 recovered 16' barrel jammed, 9' black brittle shale, 7' ss, f-ufg, hd sub ang. poor-fair por. vert frac. good odor, fluor. bleeding O & G.

Core #2 6434-43 rec. 9' ss
 ss as above bottom foot silty and tight.

D.S.T. #1 6425-37 T.O. 1' S1 15", good blow, GTS 25", 3-5' flame, rec. 216' oil, 62' HO&CCM 464' H₂O. I.F. 267, FF. 269, S1920, I.H. 3354 FH 3216
 Run 6522', 11.6 #J-55 4 1/2" new casing, w/150 sks. reg. pressured up 500# for 20" float held, wait on cement 24 hours.

AJJ	
DVR	
WRS	
HHM	
JAM	<input checked="" type="checkbox"/>
FJP	
JJD	<input checked="" type="checkbox"/>

I/We hereby swear (or affirm) that the statements herein made are a full and correct report.

APPROVED:

FEB 16 1959

Date _____
 Director A. J. Gersin

Company Oil Incorporated Date 12/18/58
 907 Walker Bank Bldg.
 Address Salt Lake City, Utah Phone No. DA 2-5547
 By James E. Wetthells Title Vice Pres
 (Signature)