

UNIT  
DEPARTMENT  
GEOLCSUBMIT IN TRIPLICATE\*  
Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS JAN 27 1976

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. COMM. AGREEMENT NAME	
2. NAME OF OPERATOR Atlantic Richfield Company		8. FARM OR LEASE NAME Sheep Mountain Unit	
3. ADDRESS OF OPERATOR 501 Lincoln Tower Bldg., 1860 Lincoln St., Denver, Colo. 80203		9. WELL NO. 5-10	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface NW NE - 640' f/North & 1330' f/East lines Sec. 10		10. FIELD AND POOL, OR WILDCAT Not Designated Area	
14. PERMIT NO. Colo. 75 789		12. COUNTY OR PARISH Huerfano	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 8304' GL, ungr.		13. STATE Colorado	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 10-27S-70W, 6th PM			

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

X

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Wells No. 1 & 3 encountered extreme difficulty due to swelling shales using a water base drilling fluid. Laboratory tests indicate this difficulty can be avoided using an invert-oil drilling fluid. It is now proposed to set surface casing using gel and lime. After setting surface, convert to an oil-invert system and drill to T.D. using an oil-invert drilling fluid.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. A. Walther, Jr.

(This space for Federal or State office use)

TITLE

Dist. Prod. &amp; Drlg. Supt.

DATE

1/26/76

APPROVED BY

M. Rogers

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DIRECTOR  
O & G CONS. COMM.

DATE

FEB 4 1976

\*See Instructions on Reverse Side

file