HIGH RESOLUTION INDUCTION ELECTRICAL LOG COMPENSATED NEUTRON LITHO-DENSITY LOG

Company: Phoenix Parent
Well: Phoenix 4-7 Sec 7-2S-2W
Field: Wildcat
County: Moffat
State: Colorado
Location: 1,980' FNL & 1,980' FWL
Sec: 7
Twp: 2S
Rge: 2W
Permanent Datum: Ground Level
Elev.: K.B. 6,000
G.L. 5,990
D.F.
Log Measured From: K.B. 10 Ft. Above Perm. Datum
Drilling Measured From: K.B.
Date: 10-Jun-2012
Run No.: ONE
Depth-Driller: 7,800
Depth-Logger: 7,800
Bottom Log Interval: 7,800
Top Log Interval: 1,000
Casing-Driller: 8.625 @ 1,000
Casing-Logger: 1,000
Bit Size: 7.875
Type Fluid in Hole: Water Based Mud
Density: 9.2
Viscosity: 40
Ph: 9.5
Fluid Loss: 6.4
Source of Sample: Flowline
Rm @ Meas. Temp.: 0.75 @ 70
Rmf @ Meas. Temp.: 0.56 @ 70
Rmc @ Meas. Temp.: 1.05 @ 70
Source of Rmf & Rmc: Measured
Rm @ BHT: 0.39 @ 160
Time Since Circulation: 4 Hrs
Max. Rec. Temp. Deg. F: 160
Equipment Number: Logger 1
Location: Craig, Colorado
Recorded By: Mark Hall
Witnessed By: Jim Smith

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions as set out in our current price schedule.

Comments:

Annular volume calculated for 4.5" casing
Tool Zero = 10 ft AGL
Thank you for using Phoenix Surveys!
API #: 05-125-34139.00000

Calibration File: 120618.ifc
Dataset Pathname: Field
Presentation Format: Combo
Dataset Creation: 18-Jun-12 07:47:03
Charted by: Depth in Feet scaled 1:240

Caliper (in) 6 16
Gamma Ray (GAPI) 0 200
SP (mV) -100 100

Deep Resistivity (Ohm-m) .2 2000
Medium Resistivity (Ohm-m) .2 2000
Shallow Resistivity (Ohm-m) .2 2000
RT (Ohm-m) .2 2000

Density Porosity (pu) 45 -15
Neutron Porosity (pu) 45 -15

1,000 ft/in (1:240)

1,000 ft/in (1:240)

Calibration File: 120618.ifc
Dataset Pathname: Field
Presentation Format: Combo
Dataset Creation: 18-Jun-12 07:47:03
Charted by: Depth in Feet scaled 1:240

Caliper (in) 6 16
Gamma Ray (GAPI) 0 200
SP (mV) -100 100

Deep Resistivity (Ohm-m) .2 2000
Medium Resistivity (Ohm-m) .2 2000
Shallow Resistivity (Ohm-m) .2 2000
RT (Ohm-m) .2 2000

Density Porosity (pu) 45 -15
Neutron Porosity (pu) 45 -15

1,000 ft/in (1:240)

Upper Sand

Lower Sand

Gamma Ray

Caliper

Logger's TD: 7800

Deep Resistivity

Medium Resistivity

Shallow Resistivity

Density Porosity

Neutron Porosity

1.65 (lst digits)

Density Porosity

Neutron Porosity