THIS DOCUMENT AND ALL INFORMATION CONTAINED HEREIN IS THE SOLE PROPERTY OF RAMWS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF RAMWS IS PROHIBITED. BY TAKING AND USING THIS DOCUMENT THE RECIPIENT AGREES TO USE THE KNOWLEDGE CONTAINED IN IT FOR THE PURPOSE AUTHORISED BY RAMWS AND NO OTHER PURPOSE. THE RECIPIENT AGREES NOT TO DISCLOSE THE CONTENTS TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF RAMWS. THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT SHALL BE RETURNED TO RAMWS ON REQUEST AND IN ANY EVENT UPON COMPLETION OF THE USE FOR WHICH IT WAS SUPPLIED.

WARRICK 7 (CDT75MM) - Continuation

NOTE: DEPTH WAS CORRELATED USING NDS ACOUSTIC CBL DATED 7-26-15

SHORT JOINT 3180' TO 3197'

MAIN PASS 3' + 10'

CBL=No + ACNTC

Company File	WHITE_ENTERPRISE_#1HA_MLTPL.DFT
Dataset Pathname	Pass1
Presentation Format	Pass 1 for 5 1/2 in 20 lb/ft Csg 4.670 in 15.500

Tool String Number	1304PAM
Pad Azimuth	0.00 deg
Pad Length	Ref. cap 15.13 ft 1825
Calibration Date	7-5
Calibration Reading	7-5 1/8
Accuracy	1 inch Continuous

Calibration Report

Repeatability Check (pre Calibration Report)

Tool String Number	1304PAM
Pad Azimuth	0.00 deg
Calibration Casing Diameter	4.670 in
Calibration Weight	15.500 lb/ft

Pipeline Calibration performed by Tue Apr 19 15:34:28 2016

Pass 1			Calibrated from		Records	
Arm	Offset	Diameter	Arm	Offset	Arm	Offset
A1	0.000	4.670	0.000	90.000	A1 000	1.000
A2	0.000	4.670	0.000	90.000	A2 000	1.000
A3	0.000	4.670	0.000	90.000	A3 000	1.000
A4	0.000	4.670	0.000	90.000	A4 000	1.000
B1	0.000	4.670	0.000	90.000	B1 000	1.000
B2	0.000	4.670	0.000	90.000	B2 000	1.000
B3	0.000	4.670	0.000	90.000	B3 000	1.000
B4	0.000	4.670	0.000	90.000	B4 000	1.000

Calibration Report

Tool String Number	1304PAM
Pad Azimuth	0.00 deg

Reference (Ref.)	Nominal (Nom.)
1.000	1.000
Max	Min
Open = 1.000	Closed = 0.000

MAIN PASS

Company File	WHITE_ENTERPRISE_#1HA_MLTPL.DFT
Dataset Pathname	Pass1
Presentation Format	Pass 1 for 5 1/2 in 20 lb/ft Csg 4.670 in 15.500
Dataset Creation	Tue Apr 19 15:34:28 2016 by Log Analyst
Charted Depth	3200 ft to 3000 ft

Time	Speed	Tension	Head Tension	Cable Speed	Line Speed	Line Tension	Weak Point
0 min	30 ft/min	1000 lb	0 lb	30 ft/min	30 ft/min	0 lb	0 lb

REPEAT PASS

Company File	WHITE_ENTERPRISE_#1HA_MLTPL.DFT
Dataset Pathname	Pass2
Presentation Format	Pass 2 for 5 1/2 in 20 lb/ft Csg 4.670 in 15.500
Dataset Creation	Tue Apr 19 16:31:10 2016 by Log Analyst
Charted Depth	3200 ft to 3000 ft

Time	Speed	Tension	Head Tension	Cable Speed	Line Speed	Line Tension	Weak Point
0 min	30 ft/min	1000 lb	0 lb	30 ft/min	30 ft/min	0 lb	0 lb

Service	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			CCL-GR 1304PAM Centralizer @ 3197.0 ft	1.58	3.66	2.24
			BTC-PIN (8 RND) Centralizer @ 3179.0 ft - 1 Joints	1.08	4.66	4.50
CCL	42.12		CCL-TOP 1304PAM Centralizer @ 3161.0 ft	1.01	4.13	38.00
			PRO-SIZ (3.5 FT) Centralizer @ 3123.0 ft - 2 Joints (Pin Down) (Pin Down)	3.00	4.38	21.42
			MAT-SW 1304SWMAT Centralizer @ 3121.0 ft	0.47	3.13	142.00
			PRO-SIZ (3.5 FT) Centralizer @ 3117.0 ft - 2 Joints (Pin Down) (Pin Down)	3.00	4.38	21.42
			PWR-SW 1304SWPWR Bow Spring @ 3098.0 ft Bow Spring @ 3098.0 ft	1.00	3.66	8.00 4.00

Tool	Length
Total	8.50
Weight	8.50
Weight	0.00
Weight	0.00
Weight	0.00