FORM 2 Rev

08/13

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

400683010

APPLICATION FOR PERMIT TO:						
▼ Drill Deepen Re-enter Recomplete and Operate						
TYPE OF WELL OIL X GAS COALBED OTHER Refiling						
ZONE TYPE SINGLE ZONE MULTIPLE ZONES COMMINGLE ZONES Sidetrack						
Well Name: Sherley Well Number: E-4-9HN						
Name of Operator: BAYSWATER EXPLORATION AND PRODUCTION LLC COGCC Operator Number: 10261						
Address: 730 17TH ST STE 610						
City: DENVER State: CO Zip: 80202						
Contact Name: Jennifer Grosshans Phone: (303)928-7128 Fax: (303)218-5678						
Email: regulatory@petro-fs.com						
RECLAMATION FINANCIAL ASSURANCE						
Plugging and Abandonment Bond Surety ID:20080034						
WELL LOCATION INFORMATION						
QtrQtr: NWNW Sec: 4 Twp: 5N Rng: 65W Meridian: 6						
Latitude: 40.434367 Longitude: -104.675158						
FNL/FSL FEL/FWL Footage at Surface: 516 feet FNL 714 feet FWL						
Field Name: GREELEY Field Number: 32760						
Ground Elevation: 4641 County: WELD						
GPS Data:						
Date of Measurement: 08/08/2014 PDOP Reading: 1.4 Instrument Operator's Name: Dallas Nielsen, C.J.						
If well is Directional X Horizontal (highly deviated) submit deviated drilling plan.						
Footage at Top of Prod Zone: FNL/FSL FEL/FWL Bottom Hole: FNL/FSL FEL/FWL						
470 FNL 1090 FWL 470 FSL 1090 FWL						
Sec: 4 Twp: 5N Rng: 65W Sec: 9 Twp: 5N Rng: 65W						
LOCATION SURFACE & MINERALS & RIGHT TO CONSTRUCT						
Surface Ownership: 🗵 Fee 🔲 State 📗 Federal 📗 Indian						
The Surface Owner is: is the mineral owner beneath the location.						
(check all that apply) is committed to an Oil and Gas Lease.						
has signed the Oil and Gas Lease.						
is the applicant.						
The Mineral Owner beneath this Oil and Gas Location is: 🗵 Fee 📗 State 🔲 Federal 📗 Indian						
The Minerals beneath this Oil and Gas Location will be developed by this Well: Yes						
The right to construct the Oil and Gas Location is granted by: Surface Use Agreement						
Surface damage assurance if no agreement is in place: Surface Surety ID:						

LEASE INFORMATION						
Using standard QtrQtr, Sec, Twp, Rng format, describe one entire mineral lease that will be produced by this well (Describe lease beneath surface location if produced. Attach separate description page or map if necessary.)						
Section 4, Township 5 North, Range 65 West: A parcel in the SW/4 See attached Lease Map.						
Total Acres in Described Lease:	28	Described Mineral Lo	ease is: 🗵 Fe	e 🔲 State	e 🗌 Federal 📗 Indian	
Federal or State Lease #		_				
Distance from Completed Portion o	f Wellbore to	Nearest Lease Line of o	lescribed lease:	0	Feet	
CULTURAL DISTANCE INFORMA	TION			INSTRUCTIONS:		
OULTONAL DIOTANOL INI ONNIA				- All measureme	ents shall be provided from center of	
Distance to nearest:					/ell to nearest of each cultural ribed in Rule 303.a.(5).	
Building:	485	Feet		- Enter 5280 for distance greater than 1 mile.		
Building Unit:	485	Feet		_	est building of any type. If nearest lding Unit, enter same distance for	
High Occupancy Building Unit:	5280	Feet		both.		
Designated Outside Activity Area:	5280	Feet		_	High Occupancy Building Unit, and side Activity Area - as defined in	
Public Road:	277	Feet		100-Series Rule	s.	
Above Ground Utility:	524	Feet				
Railroad:	3904	Feet				
Property Line:	230	Feet				
DESIGNATED SETBACK LOCATI	ON INFORM	MATION			as described in Rule 604.a.(2), within	
Check all that apply. This location is	s within a:			1	e - as described in Rule 604.a.(1),	
				within 500' of a Building Unit Urban Mitigation Area - as defined in 100-Series		
Urban Mitigation Area			ea	Rules.		
Pre-application Notifications (requir	ed if locatior	is within 1,000 feet of a	building unit):			
Date of Rule 305.a.(1) Urban I	Mitigation Ar	ea Notification to Local G	overnment:			
Date of Rule 305.a.(2) Buffer 2	Zone Notifica	tion to Building Unit Owr	ners: 08/28/20	14		
SPACING and UNIT INFORMATION	N					
Distance from Completed Portion o	f Wellbore to	Nearest Wellbore Perm	itted or Complet	ed in the same f	formation: 113 Feet	
Distance from Completed Portion o	f Wellbore to	Nearest Unit Boundary	470 Fe	et (Enter 5280 f	or distance greater than 1 mile.)	
Federal or State Unit Name (if appl): Unit Number:						
SPACING & FORMATIONS COMMENTS						
Nearest wellbore permitted or completed in the same formation is Harrell 4-52 API #05-123-30738.						
Niobrara: Proposed Spacing Unit is described as W/2 of Section 4 and 9, T5N, R65W						
OBJECTIVE FORMATIONS						
Objective Formation(s) Formation	n Code	Spacing Order Number(s)	Unit Acreage A	ssigned to Well	Unit Configuration (N/2, SE/4, etc.)	
NIOBRARA NBRR			64	40	GWA	
DRILLING PROGRAM						
Proposed Total Measured Depth:16851 Feet						
Distance to nearest permitted or	existing well	bore penetrating objectiv	e formation:	113 Feet (Including plugged wells)	
Will a closed-loop drilling system	be used?	Yes		_		
Is H ₂ S gas reasonably expected to be encountered during drilling operations at concentrations greater than						

1, 40		(1/1)	1100 D :	· 0 Bl				
or equal to 100 ppm? No (If Yes, attach an H2S Drilling Operations Plan)								
Will salt sections be encountered during drilling? No								
Will salt based (>15,000 ppm Cl) drilling fluids be used? No								
Will oil based	drilling fluids b	be used? No						
BOP Equipme	ent Type: 🔀	Annular Preventor	⊠ Double	Ram 🗵 R	otating Head	Non	е	
GROUNDWATE	ER BASELINE	SAMPLING AND	MONITORIN	IG AND WATER \	WELL SAMPLIN	G		
Water well sa	mpling require	d per Rule 318	BA					
DRILLING WAS	STE MANAGE	MENT PROGRAM						
Drilling Fluids	Disposal:	OFFSITE	Drilling Flu	uids Disposal Meth	ods: Land applic	ation		
Cuttings Dispo	osal: OFF	SITE	Cutt	tings Disposal Met	hod: Other			
Other Dispose	al Description:							
Cuttings will b	e disposed of	by land farming.						
Beneficial r	euse or land a	pplication plan sub	mitted? Y	es				
Reuse Fa	cility ID: 43	5839 or Do	cument Num	nber:				
CASING PROG	RAM							
Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
SURF	12+1/4	9+5/8	36	0	800	355	800	0
1ST 1ST LINER	8+3/4	7 4+1/2	26	0	7424	581	7424	400
Conductor (6+1/8		11.6	7124	16851	785	16851	6724
		CATION EXCEPT	ONS					
		CATION EXCEPT	ONS					
Check all that ap		_						
	. ,	on Zone (within 500	•	•		D :		
		on Location (existir	ig or approve	ed Oil & Gas Locat	tion now within a	Designated Se	etback as a re	sult of
Rule 604.a	•							
	o.(1)B. Exception on after Location	on Location (existir on approval)	ig or approve	ed Oil & Gas Locat	tion is within a De	esignated Setb	ack due to Bu	ilding Unit
Rule 604.b	o.(2) Exception	Location (SUA or	site-specific o	development plan	executed on or b	efore August 1	, 2013)	
Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013) Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific								
development plan) GREATER WATTENBERG AREA LOCATION EXCEPTIONS								
Check all that apply:								
Rule 318A.a. Exception Location (GWA Windows). Rule 318A.c. Exception Location (GWA Twinning).								
RULE 502.b VARIANCE REQUEST								
Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number								

OTHER LOC	CATION EXCEPTIONS					
Check all tha	at apply:					
Rule 3	318.c. Exception Location from Rule or Spacir	ng Order Nu	mber			
Rule 6	603.a.(2) Exception Location (Property Line S	etback).				
	otions and variances require attached Reques ertifications, SUAs).	t Letter(s). I	Refer to applica	ble rule for ac	dditional required atta	chments (e.g.
OPERATOR	COMMENTS AND SUBMITTAL					
Comments	Distance to nearest permitted or existing we	Ilbore penet	rating objective	formation is t	he Harrell 4-52 API #	05-123-30738.
	Letter to Director for COGCC Rule 318A.e. I	Proposed Sp	pacing Unit, atta	ached as Prop	oosed Spacing Unit.	
	Letter to Director for COGCC Rule 318A.m.	Minimum In	trawell Distance	e, attached as	Anti-Collision Waive	r
	Waiver from Great Western Operating Comp	pany, LLC fo	or Harrell 4-52 is	s attached as	Anti-Collision Waiver	
	The Building Unit that is 500' from the propo Ms.Sherley the Building Unit is an abandone					j to
	Surface Use Agreement is attached as, Surf	face Agrmt/S	Surety.			
This applica	ation is in a Comprehensive Drilling Plan		CDP #:			
Location ID:	_				_	
	ication being submitted with an Oil and Gas L	ocation Ass	essment applica	ation?	Yes	
	ertify all statements made in this form are, to the					
Signed:			Print Name:	Jennifer Gros	shans	
Title: I	Regulatory Analyst	Date:	12/9/2014	Email:	regulatory@petro-fs	s.com
water right law. Operat	nust have a valid water right or permit allowi or permit allowing for industrial use, otherw tor must also use the water in the location s e in place of use is required under Colorado	rise an appli set forth in th	cation for a char ne water right o	ange in type decree or we	of use is required ur Il permit, otherwise a	nder Colorado
Based on the	e information provided herein, this Application y approved.	for Permit-t	o-Drill complies	with COGCC	Rules and applicable	e orders
COGCC App	1 1 1	Dire	ector of COGC	C Date:	1/12/2015	
	API NUMBER		Exp	oiration Date:	01/11/2017	
05 123						

Conditions Of Approval

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

COA Type	<u>Description</u>
	Open hole resistivity and gamma logs shall be run to describe the stratigraphy of the entire well bore and to adequately verify the setting depth of surface casing and aquifer coverage. On a multi-well pad, these open hole logs are only required on one of the first wells drilled on the pad and the Drilling Completion Report - Form 5 for every well on the pad shall identify which well was logged.
	Operator shall comply with Buffer Zone Move-In, Rig-Up Notice Rule 305.h (effective 9/30/2014).
	 Submit Form 42 electronically to COGCC 48 hours prior to MIRU. Comply with Rule 317.i and provide cement coverage from end of 7" casing to a minimum of 200' above Niobrara. Verify coverage with cement bond log. Run and submit Directional Survey from TD to base of surface casing. The operator shall comply with Rule 321, and it shall be the operator's responsibility to ensure that the wellbore complies with setback requirements in commission orders or rules prior to producing the well.

Best Management Practices

<u>No</u>	BMP/COA Type	<u>Description</u>
1	Planning	Multi-well Pads are located in a manner which allows for resource extraction while maintaining the highest distances possible from the offsetting residential areas and complies with the wishes of the surface owner.
		A meeting with the surface owner will determine the fencing plan.
2	Traffic control	Access Roads: The access road will be constructed to accommodate local emergency vehicles. This road will be maintained for access at all times. Traffic will be routed to minimize local interruption.
Visual Impacts: All long term facility structures will be painted a color that enable facilities to blend in with the natural background color of the landscape, as seen viewing distance and location typically used by the public. Maintain appearance garbage clean-up; a trash bin will be located on site to accumulate waste by the personnel drilling the wells. Site will have unused equipment, trash and junk rer immediately. Operators shall keep the Surface Use Area as well as any roads or other areas to provide the surface of t		
		Operator safe and in good order, including control of noxious weeds litter and debris.
4	Storm Water/Erosion Control	Use water bars, and other measures to prevent erosion and non-source pollution. Implement and maintain BMPs to control stormwater runoff in a manner that minimizes erosion, transport of sediment offsite, and site degradation. Co-locate gas and water gathering lines whenever feasible, and mitigate any erosion problems that arise due to the construction of any pipeline(s).
5	Material Handling and Spill Prevention	Leak Detention Plan: Pumper will visit the location daily and visually inspect all tanks and fittings for leaks. Additionally, monthly documented SPCCP inspections are conducted pursuant to 40 CFR 112.
		Control of fire hazards: All material that is considered a fire hazard shall be a minimum of 25' from the wellhead tanks or separators. Electrical equipment shall comply with API IRP 500 and will comply with the current national electrical code.
		Operator shall comply with state and federal laws, rules and regulations governing the presence of any petroleum products, toxic or hazardous chemicals or wastes on the Subject lands. equipment.

6	Dust control	Fugitive dust will be controlled by speed restrictions on all neighboring roads, regular road maintenance and repair, and avoiding construction activity during high wind days. If technologically and economically feasible, additional management practices may also be required to minimize fugitive dust as well as to control silica dust while handling sand during frac'ing operations.
7	Construction	Remove only the minimum amount of vegetation necessary for the construction of roads and facilities. Conserve topsoil during excavation and reuse as cover on disturbed areas to facilitate regrowth of vegetation. No construction or routine maintenance activities will be performed during periods when the soil is too wet to adequately support construction equipment.
8	Noise mitigation	The drill site will be powered by electricity, mitigating the majority of noise from drilling operations. Sound walls and/or hay bales will be used to surround the well site during drilling operations.
9	Drilling/Completion Operations	Anti-Collision: Prior to drilling operations, Operator will perform an anti-collision scan of existing offset wells that have the potential of being within close proximity of the proposed wells. The anti-collision scan may include definitive MWD or gyro surveys of the offset wells with included error of uncertainty per survey instrument, and compared against the proposed well path with its respective error of uncertainty. If current surveys do not exist for the offset wells, operators may have gyro surveys conducted to verify bottom hole location. The proposed well may only be drilled if the anti-collision review results indicate that the risk of collision is sufficiently low as defined by the anticollision plan, with separation factors greater than 1.5, or if the risk of collision has been mitigated through other means including shutting in wells, plugging wells, increased drilling fluid in the event of lost returns or as is appropriate for the specific situation. In the event of an increased risk of collision, that risk will be mitigated to prevent harm to people, the environment or property. For the proposed well, upon conclusion of drilling operations, an as-constructed directional survey will be submitted to the COGCC with the Form 5. Identification of plugged and abandoned wells will be identified pursuant to 319.a.(5)
10	Drilling/Completion Operations	A closed –loop system will be used for drilling operations. Blowout Prevention Equipment ("BOPE"): A double ram and annular preventer will be used during drilling. Stabbing valves shall be installed in the event of reverse circulation and shall be prior tested with low and high pressure fluid. Lighting: Light sources during all phases of operations will be directed downwards and away from occupied structures where possible. Once the drilling and completion rigs leave the site, there will be no permanently installed lighting on site. Bradenhead Monitoring: Operator acknowledges and will comply with COGCC Policy for Bradenhead Monitoring during Hydraulic Fracturing Treatments in the GreaterWattenberg Area dated May 29, 2012.
11	Interim Reclamation	Operator shall be responsible for segregating the topsoil, backfilling, repacking, reseeding, and recontouring the surface of any disturbed area so as not to interfere with Owner's operations and shall reclaim such area to be returned to pre-existing conditions as best as possible with control of all noxious weeds.
12	Final Reclamation	Within 90 days subsequent to the time of plugging and abandonment of the entire site, superfluous debris and equipment shall be removed from the site. The Operator shall restore the surface of the Land affected by such terminated operations as near as possible to the previous state that existed prior to operations.

Total: 12 comment(s)

Applicable Policies and Notices to Operators

Notice Concerning Operating Requirements for Wildlife Protection.

Policy for Bradenhead Monitoring During Hydraulic Fracturing Treatments in the Greater Wattenberg Area.

Attachment Check List

Att Doc Num	<u>Name</u>
400683010	FORM 2 SUBMITTED
400747943	OffsetWellEvaluations Data
400748011	DIRECTIONAL DATA
400748012	DEVIATED DRILLING PLAN
400748013	WELL LOCATION PLAT
400748016	LEASE MAP
400748017	SURFACE AGRMT/SURETY
400748020	PROPOSED SPACING UNIT
400748024	ANTI-COLLISION WAIVER
400748026	ANTI-COLLISION WAIVER

Total Attach: 10 Files

General Comments

<u>User Group</u>	Comment	Comment Date
#Error	Final Review Completed. No LGD or public comment received.	1/7/2015 8:32:55 AM
#Error	Offset Wells Evaluated	12/11/2014 7:10:48 AM
#Error	Passed completeness.	12/10/2014 9:21:10 AM

Total: 3 comment(s)