# *Clough NR 343-3 Wellbore Diagram*

| Well | Pad | API |
|---|---|---|
| Clough NR 343-3 | NR 23-3 | 05-045-23910 |

| Diagram Date | Spud Date | First Production Date |
|---|---|---|
| 2/27/2019 | 10/3/2018 | 2/5/2019 |

| Location | Meridian | County |
|---|---|---|
| NESW | 6th | Garfield |


| Top Perf | Bottom Perf | Current EOT |
|---|---|---|
| 7,082 | 10,457 | 10,109 |

| Bottom Surf Csg | Bottom Prod Csg | TOC |
|---|---|---|
| 1,138 | 10,610 | 2,450 |

| TD | TVD | Elevation |
|---|---|---|
| 10,610 | 9,957 | 6,719 |

| PBTD | PBTVD | KB |
|---|---|---|
| 10,566 | 9,913 | 6,743 |

| Formation Tops | |
|---|---|
| Wasatch | |
| Wasatch G | 3,795 |
| Mesaverde | 6,707 |
| Ohio Creek | 6,707 |
| Williams Fork | 6,830 |
| Cameo | 9,637 |
| Rollins | 10,524 |
| Cozzette | |
| Corcoran | |
| Sego | |




| Conductor: | |
|---|---|
| Hole size | 26 |
| Casing size | 18 |
| Weight | 47.44 |
| Depth | 108 |
| Cement Sks | 180 |

| Surface Csg: | |
|---|---|
| Hole size | 13.5 |
| Casing size | 9 5/8 |
| Weight | 36 |
| Depth | 1128 |
| Cement Sks | 300 |

| Prod. Csg: | |
|---|---|
| Hole size | 8 3/4 |
| Casing size | 4 1/2 |
| Weight | 11.6 |
| Depth | 10600 |
| Cement Sks | 1415 |

End of Tbg
10,109

End of Csg
10,610