



Job Number: SVGJ-180069 - API: 05-123-20645

Company: PDC

Lease/Well: Knox 32-3

Location: Weld County, CO

Rig Name: N/A

RKB: 0'

G.L. or M.S.L.: GL

State/Country: Colorado/USA

Declination: 8.352°

Grid: East To True North

File name: C:\WINSER~1\2018\PDC\GJ\KNOX\323.SVY

Date/Time: 03-May-18 / 14:27

Curve Name: Surface - 7600' M.D. (Rate Gyro)

Lat: 40.43128 Long: -104.87439

MS Directional

WINSERVE SURVEY CALCULATIONS
 Minimum Curvature Method
 Vertical Section Plane .00
 Vertical Section Referenced to Wellhead
 Rectangular Coordinates Referenced to Wellhead

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
100.00	1.68	44.49	99.99	1.05	1.03	1.05	1.47	44.49	1.68
200.00	1.51	42.13	199.95	3.07	2.94	3.07	4.25	43.76	.18
300.00	1.45	48.97	299.91	4.88	4.78	4.88	6.83	44.41	.19
400.00	1.54	50.22	399.88	6.57	6.76	6.57	9.43	45.85	.10
500.00	1.26	50.14	499.85	8.13	8.64	8.13	11.86	46.74	.28
600.00	1.33	56.89	599.82	9.47	10.46	9.47	14.11	47.84	.17
700.00	1.13	47.66	699.80	10.77	12.16	10.77	16.24	48.47	.28
800.00	1.07	52.08	799.78	12.01	13.62	12.01	18.16	48.61	.10
900.00	.89	40.25	899.77	13.17	14.86	13.17	19.86	48.45	.27
1000.00	.59	36.17	999.76	14.18	15.67	14.18	21.13	47.85	.30
1100.00	.50	14.54	1099.76	15.02	16.08	15.02	22.00	46.96	.22
1200.00	.52	14.47	1199.75	15.88	16.30	15.88	22.76	45.75	.02

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
1300.00	.52	325.86	1299.75	16.70	16.16	16.70	23.24	44.07	.43
1400.00	.62	307.22	1399.74	17.40	15.48	17.40	23.29	41.65	.21
1500.00	.82	291.15	1499.73	17.98	14.38	17.98	23.02	38.64	.28
1600.00	1.16	287.27	1599.72	18.54	12.74	18.54	22.50	34.50	.35
1700.00	1.30	283.38	1699.70	19.11	10.67	19.11	21.89	29.19	.16
1800.00	1.50	291.64	1799.67	19.85	8.35	19.85	21.54	22.82	.28
1900.00	1.76	285.13	1899.63	20.73	5.65	20.73	21.49	15.26	.32
2000.00	1.97	278.09	1999.57	21.38	2.47	21.38	21.52	6.59	.31
2100.00	2.21	279.31	2099.51	21.93	-1.13	21.93	21.96	357.04	.24
2200.00	2.19	288.91	2199.43	22.86	-4.84	22.86	23.37	348.04	.37
2300.00	1.97	298.23	2299.37	24.29	-8.17	24.29	25.63	341.42	.40
2400.00	1.81	301.40	2399.31	25.93	-11.03	25.93	28.18	336.96	.19
2500.00	1.79	303.22	2499.26	27.61	-13.68	27.61	30.81	333.64	.06
2600.00	1.88	306.25	2599.21	29.43	-16.31	29.43	33.65	331.01	.13
2700.00	1.87	306.45	2699.16	31.37	-18.95	31.37	36.65	328.87	.01
2800.00	1.64	302.53	2799.11	33.11	-21.47	33.11	39.46	327.05	.26
2900.00	1.42	301.72	2899.08	34.53	-23.73	34.53	41.90	325.51	.22
3000.00	1.09	301.93	2999.05	35.69	-25.59	35.69	43.91	324.36	.33
3100.00	1.23	298.54	3099.03	36.70	-27.34	36.70	45.77	323.32	.16
3200.00	2.33	284.27	3198.98	37.72	-30.25	37.72	48.35	321.27	1.18
3300.00	2.40	279.05	3298.90	38.55	-34.29	38.55	51.59	318.35	.23
3400.00	2.37	280.84	3398.81	39.27	-38.39	39.27	54.91	315.65	.08
3500.00	2.50	280.18	3498.72	40.04	-42.56	40.04	58.44	313.25	.13
3600.00	2.49	276.98	3598.63	40.69	-46.87	40.69	62.07	310.96	.14
3700.00	2.40	278.91	3698.54	41.28	-51.09	41.28	65.68	308.94	.12
3800.00	2.46	280.47	3798.45	41.99	-55.27	41.99	69.41	307.23	.09
3900.00	2.31	281.33	3898.36	42.78	-59.36	42.78	73.17	305.78	.15
4000.00	.60	239.79	3998.32	42.91	-61.79	42.91	75.23	304.78	1.90
4100.00	.95	151.75	4098.32	41.92	-61.85	41.92	74.71	304.13	1.11
4200.00	.84	162.78	4198.31	40.49	-61.24	40.49	73.41	303.47	.20
4300.00	1.08	169.39	4298.29	38.86	-60.85	38.86	72.20	302.56	.26
4400.00	1.27	186.42	4398.27	36.83	-60.80	36.83	71.08	301.21	.40
4500.00	2.10	212.00	4498.23	34.18	-61.89	34.18	70.70	298.91	1.10
4600.00	2.15	216.00	4598.16	31.11	-63.96	31.11	71.13	295.93	.16

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
4700.00	1.97	234.71	4698.10	28.60	-66.47	28.60	72.36	293.28	.69
4800.00	1.78	234.15	4798.04	26.69	-69.13	26.69	74.11	291.11	.19
4900.00	1.35	237.51	4898.00	25.15	-71.38	25.15	75.69	289.41	.44
5000.00	1.17	239.62	4997.98	24.00	-73.26	24.00	77.09	288.14	.19
5100.00	1.15	225.44	5097.96	22.78	-74.85	22.78	78.24	286.93	.29
5200.00	.62	210.34	5197.95	21.61	-75.84	21.61	78.86	285.90	.57
5300.00	.63	215.78	5297.94	20.70	-76.44	20.70	79.19	285.15	.06
5400.00	1.20	193.29	5397.93	19.23	-77.00	19.23	79.37	284.02	.66
5500.00	2.30	206.58	5497.88	16.42	-78.14	16.42	79.84	281.87	1.17
5600.00	1.66	175.62	5597.82	13.18	-78.93	13.18	80.02	279.48	1.22
5700.00	1.41	167.54	5697.79	10.53	-78.55	10.53	79.25	277.64	.33
5800.00	1.10	156.97	5797.76	8.45	-77.91	8.45	78.37	276.19	.39
5900.00	1.11	152.49	5897.75	6.71	-77.09	6.71	77.38	274.97	.09
6000.00	1.32	152.56	5997.72	4.83	-76.11	4.83	76.26	273.63	.21
6100.00	1.38	154.02	6097.70	2.72	-75.05	2.72	75.10	272.08	.07
6200.00	1.03	150.02	6197.67	.86	-74.07	.86	74.08	270.66	.36
6300.00	1.05	144.77	6297.66	-.67	-73.10	-.67	73.10	269.48	.10
6400.00	1.05	156.57	6397.64	-2.26	-72.20	-2.26	72.24	268.21	.22
6500.00	.89	154.27	6497.63	-3.80	-71.50	-3.80	71.60	266.96	.16
6600.00	.98	153.78	6597.61	-5.26	-70.79	-5.26	70.98	265.75	.09
6700.00	1.07	175.51	6697.60	-6.96	-70.34	-6.96	70.68	264.35	.40
6800.00	1.01	161.76	6797.58	-8.73	-69.99	-8.73	70.53	262.89	.26
6900.00	1.10	171.56	6897.56	-10.52	-69.57	-10.52	70.36	261.40	.20
7000.00	.41	157.14	6997.55	-11.80	-69.29	-11.80	70.29	260.34	.71
7100.00	.70	143.92	7097.55	-12.62	-68.79	-12.62	69.94	259.61	.32
7200.00	.73	141.44	7197.54	-13.61	-68.03	-13.61	69.38	258.69	.04
7300.00	.65	142.12	7297.53	-14.56	-67.29	-14.56	68.85	257.79	.08
7400.00	.74	124.32	7397.53	-15.37	-66.41	-15.37	68.16	256.97	.23
7500.00	.53	116.07	7497.52	-15.94	-65.46	-15.94	67.37	256.32	.23
Last Survey Depth Recorded									
7600.00	.36	74.84	7597.52	-16.06	-64.74	-16.06	66.70	256.07	.35