PROFILE

COMPANY	CHEVRON USA INC.
WELL NAME & NUMBER	A.G. MCLAUGHLIN 74X
FIELD	RANGELY
COUNTY	RIO BLANCO
STATE	COLORADO
DATE	01-26-96 ☐ NEW ☒ W.O.

		TUBING	TUBING
SIZE		2 7/8	2 3/8
WEIGHT	23&26	7.55	4.7
GRADE	K-55	DYB J-55	9Cr 1 Mo
THREAD		EUE	EUE
DEPTH		CEMENT LINED	



ITEM	DESCRIPTION	MAX. O.D. INCHES	MIN. I.D. INCHES	LENGTH FEET	DEPTH FEET
*	K.B.			14.90	
*	COMPRESSION (14,000#)			-1.50	13.40
1	2 7/8 EUE PXP S.S. SHS	3.063	2.128	.33	13.73
2	1 Jnt. 2 7/8 DYB C.L. Tubing	3.668	2.128	30.38	44.11
3	2 7/8 X 10 Ft. C.L. Pup Jnt. IDLE	3.668	2.128	10.11	54.22
4	2 7/8 X 8 Ft. C.L. Pup Jnt. SHS	3.668	2.128	8.21	62.43
5	2 7/8 X 6 Ft. C.L. Pup Jnt. IDLE	3.668	2.128	6.17	68.60
6	2 7/8 X 4 Ft. C.L. Pup Jnt. IDLE	3.668	2.128	3.86	72.46
7	192 Jnts. 2 7/8 C.L. Tubing DYB	3.668	2.128	5876.77	5949.23
8	2 7/8 EUE BXP S.S. SHS	3.668	2.128	.75	5949.98
9	47B4 FH Pkr. PA-400 I&E NEW	6.078	2.401	7.30	5957.28
10	1 Jnt. 2 7/8 FGW & TK-69 Int.	3.868	2.401	30.41	5987.69
11	OTIS SLICK RH ON & OFF W/ 1.875 X	5.75	1.875	2.24	5989.93
12	2 3/8 X 6 Ft. Pup Jnt. 9 Cr 1 Moly			6.00	5995.93
13	47B4 FH Pkr. 9 c r 1 Moly			8.00	6003.93
14	4 Jnts. 2 3/8 9 Cr 1 Moly Tubing			126.66	6130.59
15	Otis sidepoket Mandrel # 215-WNC-1002			5.65	6136.24
16	2 3/8 X 6 Ft. Pup Jnt. 9 Cr 1 Moly			6.00	6142.24
17	47B4 FH Pkr. 9 Cr 1 Moly			8.00	6150.24
18	2 Jnts. 2 3/8 Tubing 9 Cr 1 Moly			63.15	6213.39
19	Otis Sidepocket Mandrel # 215-WNC-1002			5.65	6219.04
20	2 3/8 X 6 Ft. Pup Jnt. 9 Cr 1 Moly			6.00	6225.04
21	47B4 FH Pkr. 9 Cr 1 Moly			8.00	6233.04
22	2 3/8 X 4 Ft Pup Jnt. 9 Cr 1 Moly			4.00	6237.04
23	6 Jnts. 2 3/8 Tubing 9 Cr 1 Moly			188.68	6425.72
24	Otis Sidepocket Mandrel # 215-WNC-1002			5.65	6431.37
25	2 3/8 X 10 Ft. Pup Jnt. 9 Cr 1 Moly			10.00	6441.37
26	47B4 FH Pkr. 9 Cr 1 Moly			8.00	6449.37
27	3 Jnts. 2 3/8 Tubing 9 Cr 1 Moly			94.78	6544.15
28	Otis Sidepocket Mandrel 215-WNC-1002			5.65	6549.80
29	2 3/8 X 6 Ft. Pup Jnt. 9 Cr 1 Moly			6.00	6555.80
30	Otis 1.875 XN Nipple 9 Cr 1 Moly			1.20	6557.00
	TUBING LANDED W/ 14,000# Compression				
	TUBING TESTED 2500 PSI W/ 120 PSI Bleed Off				
	CASING TESTED 750 PSI W/ 0 Bleed Off				
	Tbg. made up to 1250 Ft. Lbs Torque & Box & Pins Doped				
	7" 23# K-55 0 To 5322				
	7" 26# K-55 5322 To 6649				
	Top Perf. @ 6038				
	Btm. Perf. @ 6549				
	P.B.T.D. @ 6589				
	1.875 X Plug Lost 01-23-96 Poss. on FH pkr. # 13				
	ITEMS # 12 Thru # 30 Ran 03-20-89				

PREPARED FOR: DOYLE OLREE

PREPARED BY: Gary L. Workman | OFFICE: Vernal, Utah | PHONE: 801-789-5918

BAKER OIL TOOLS

COMPLETIONS BY BAKER

BAKER DIVISION

BAKER OIL TOOLS, INC.

HOUSTON • LOS ANGELES •