



99999999

RECEIVED
CONSERVATION COMMISSION OCT 29 1981

NT OF NATURAL RESOURCES

STATE OF COLORADO

OIL & GAS CONS. COM.

SCANNED

121-09388

File in duplicate for Patented and Federal lands.
File in triplicate for State lands.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO.	
2. NAME OF OPERATOR Timca Resources Ltd		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Rt. 4, 13479 Road 37, Sterling, Colorado 80751		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660 ft. FSL At proposed prod. zone 1980 ft. FEL C-SW SE		8. FARM OR LEASE NAME Mitchell	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4536' KB 4526' GL		10. FIELD AND POOL, OR WILDCAT Stony Point	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 20-2N-54W	
		12. COUNTY Washington	13. STATE Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date of work _____

Plan to retrieve as much casing as possible and plug as follows:

1. Spot first plug opposite "D" sand perforated interval
2. Spot second plug in and out bottom of casing @ 94'
3. Set third plug (10 sacks) at top of surface casing.
4. Cut off surface casing three feet below surface and weld on cap.

DVR	
FIP	
HHM	<input checked="" type="checkbox"/>
JAM	<input checked="" type="checkbox"/>
JUD	<input checked="" type="checkbox"/>
RLS	
CON	



00085245

18. I hereby certify that the foregoing is true and correct

SIGNED

Tim C. Smith

TITLE President

DATE 10-20-81

(This space for Federal or State office use)

APPROVED BY

John Rogers

DIRECTOR

TITLE

DATE

OCT 30 1981

CONDITIONS OF APPROVAL, IF ANY: